RMCAO CHECKLIST FOR CONCRETE PUMPING

Project:											
Location:											
Directions:											
1. Contacts											
Who			Name		one	N	lobile		Fax		E-Mail
C. Contractor											
RMC Supplier											
Pump Contractor											
2. General Condition	ons										
		Pump:		am/pm		Co	Concrete:			am/pm	
		 □ Slabs		□ Walls				☐ Footings			Other
Placement Rate (m³/hr.)				Volume (m³)							
Type of Pump		☐ Regular		☐ Z-Boom			☐ Telescoping		ıg	☐ Trailer	
Size of Pump (m)				Pipeline dia, mm		n					
Pumping Distance (m)		/ertical					Н	Horizontal			
Slump/Air Spec		☐ Point o	ge	je			Poir	ent			
Testing		Point of Discharge					☐ Point of Placement				
Priming Agent] Grout					☐ Slick Pack					
3. Concrete Mixture	۵										
Strength (MPa)		28 days:	Ot			Other					
Max Size of Aggregate (mm)							3 pipeline diameter)				
Density (kg/m³)		 			ĺ		☐ Yes		1	□ No	
Slump (mm)				Air (%)							
Water Reducer		☐ Regular		☐ MRWR		☐ HRWR					
Fibres		☐ Yes		□ No							
Special Requirements											
Set Time Requirements (hr.)		Initial:		F		Final:	inal:				
Water Addition Permitted		☐ Yes		□ No							
4. Jobsite/Safety											
Wash Out Area			☐ Yes		□ No		Locatio	n.			
Power Lines			☐ Yes		□ No			/11.			
Safe Set Up Area		☐ Yes			 		Restrictions:				
Clean Water Available	out			□ No							
Cicaii Water Available	. J. VVUJI		res								

5. Notes